ANTIFOULING COATING COMPOSITION

Patent Number:

JP11335619

Publication date:

1999-12-07

Inventor(s):

NITTA TOMOHISA; TONOMURA SADAICHI; TOKIDA KAZUYOSHI; SASAKI HIROJI

Applicant(s):

DAINIPPON TORYO CO LTD

Requested Patent:

√ JP11335619

Application Number: JP19980146947 19980528

Priority Number(s):

IPC Classification:

C09D143/04; C09D5/16; C09D157/04

EC Classification:

Equivalents:

Abstract

PROBLEM TO BE SOLVED: To obtain an antifouling coating composition capable of keeping the antifouling performance over a long period by the slow dissolution of the coating film in seawater after forming a coating film by adding a carboxy- containing monobasic acid to an antifouling coating material composed of specific

SOLUTION: This antifouling coating composition contains (A) a copolymer of (i) one or more kinds of monomers expressed by the formula (R1 is H or CH3; R2 to R4 are each 1-18C alkyl, a cycloalkyl or an aryl) and (ii) one or more kinds of other ethylenic unsaturated monomers copolymerizable with the component (i), (B) a monobasic acid containing carboxy group and (C) a metal-containing antifouling agent. The amount of the component (i) is preferably 5-80 wt.% of the total monomer of the component A and the weight- average molecular weight of the component A is preferably 1,000-100,000. The ratio of the total number of carboxy groups bonded with triorganosilyl groups in the component A to the total number of carboxy groups in the component B is preferably 0.3-3.0.

Data supplied from the esp@cenet database - I2